



## MODEL 2M214 Series

### FEATURES


- Light-weight, compact, and cost-effective construction.
- Sufficiently suppressed noise spectrum.
- Stable performance and good reliability



2M214-04TYPE



2M214-15TYPE



2M214-35TYPE

### 1. General Data

#### ELECTRICAL CHARACTERISTICS

Filament voltage .....	3.3Vac
Filament current.....	10.0Aac
Frequency(with matched load).....	2460MHz
Anode potential .....	Earth
Filament potential .....	(-4kV)
Magnet .....	Ferrite - magnet

#### MECHANICAL CHARACTERISTICS

Width .....	80.0mm(3.15inches) max.
Length .....	127mm(5.00inches) max.
Height.....	133mm(5.24inches) max.
Weigh .....	Approx. 0.8Kg
Mounting position .....	Any
Cooling .....	Forced air

### 2. Absolute Maximum Ratings

#### ELECTRICAL CHARACTERISTICS

	Min	Max	Unit
Filament Voltage .....	2.85	3.75	Vac
Pre - heating Time .....	0	-	Sec
Average Anode Current.....	-	350	mAdc
Peak anode current .....	-	1200	mAp
Average anode input .....	-	1400	W
Load VSWR(continuous) .....	-	4	-
Load VSWR.instantaneous).....	-	8	-
Anode core temperature .....	-	300	°C
Temperature .....	-30	60	°C

### 3. Typical Operation

#### OPERATING CONDITIONS

Filament voltage .....	3.3Vac
Average anode current # .....	300mAdc
Cooling air flow .....	1.0m³/min
# Power supply unit:Half-wave doubler with leakage transformer or full-wave rectifier without filter.	

#### TYPICAL PERFORMANCE

Frequency(matched load) .....	2460MHz
Peak anode voltage .....	4.20kVp
Average output power(matched load) .....	1000W
Average output power(in a typical oven) .....	850W*

\*In accordance with IEC Pub. 705 measurement method.